


C128 Injector Driver Module (IDM)



C128
INJECTOR DRIVER MODULE (IDM)

PIN	CIRCUIT	CIRCUIT FUNCTION	PIN	CIRCUIT	CIRCUIT FUNCTION
1	—	NOT USED	21	557 (BR/Y)	Fuel Injector #3
2	359 (GY/R)	Signal Return	22	556 (W)	Fuel Injector #2
3	—	NOT USED	23	878 (PK/Y)	Fuel Injector Feed #2, 4, 6, 8
4	818 (GY/W)	Electronic Feed Back Signal Output	24	1087 (C)	Fuel Injector Feed #1, 3, 5, 7
5	—	NOT USED	25	—	NOT USED
6	555 (T)	Fuel Injector #1	26	570 (BK/W)	Ground
7	558 (BR/LB)	Fuel Injector #4	27	—	NOT USED
8	559 (T/BK)	Fuel Injector #5	28	—	NOT USED
9	562 (LB)	Fuel Injector #8	29	—	NOT USED
10	—	NOT USED	30	—	NOT USED
11	—	NOT USED	31	—	NOT USED
12	—	NOT USED	32	—	NOT USED
13	—	NOT USED	33	—	NOT USED
14	876 (DG/LG)	Power Input	34	—	NOT USED
15	—	NOT USED	35	—	NOT USED
16	817 (Y/LB)	Cylinder Identification Signal Input	36	—	NOT USED
17	821 (BR/C)	Fuel Delivery Command Signal Input	37	—	NOT USED
18	48	Injector Shield Ground	38	—	NOT USED
19	560 (LG/O)	Fuel Injector #6	39	—	NOT USED
20	561 (T/R)	Fuel Injector #7	40	—	NOT USED